Nobeyama Radio Polarimeters (NoRP) Analysis Manual ver. 2.1

Nobeyama Radio Observatory / NAOJ

February 3, 2010

Contents

1 Change Log **3**

2 Introduction **3**

3 How to setup **3**

4 Analysis **3**

4.1 Start Analysis . . . 3
4.2 Database . . . 4
4.2.1 Event List . . . 4
4.2.2 Daily Averaged Flux . . . 4
4.3 Where is the Data ? . . . 4
4.3.1 Calibrated Data in XDR (IDL save) format . . . 4
4.3.2 Raw Data . . . 5
4.4 Read the Data — Nobeyama Radio Polarimeters . . . 5
4.5 Read the Data — Toyokawa Radio Polarimeters . . . 5
4.6 Plot . . . 6
4.7 Spectrum Analysis . . . 6
4.7.1 Optically-Thin Non-Thermal Gyrosynchrotron Emission (Preliminary) . . . 6
4.7.2 Optically-Thin Thermal Free-Free Emission (Preliminary) . . . 7
4.8 Example of Analysis Session . . . 7
4.8.1 Choose an Event . . . 7
4.8.2 Light Curves . . . 7
4.8.3 Spectrum Analysis . . . 7
4.9 Others . . . 8
4.9.1 Read Raw Data Directly . . . 8

A NoRP data archive: anonymous FTP **8**

B Acknowledgement **8**

1 Change Log

- Version 1.0e: 21 December 2000, written by Yokoyama, T.
- Version 2.0e: 7 September 2007, written by Meshalkina, N.
- Version 2.1e: 3 Feburary 2010, modified by Shimojo, M.

2 Introduction

This is a manual for analysis of the data obtained by Nobeyama Radio Polarimeters (NoRP; Nakajima et al. 1985) and Toyokawa Radio Polarimeters (TYKW; Torii et al. 1979; Shibasaki et al. 1979).

For any questions and requests, please send an e-mail to

`service@solar.nro.nao.ac.jp`

The latest information on NoRP is updated on NRO solar web site. The URL is

`http://solar.nro.nao.ac.jp/norp/`

3 How to setup

(1) Installation of the *SolarSoftware*.

Install the SolarSoftware (SSW) with the subpackage 'Radio/NoRP'. We strongly recommend to install the SolarSoftware with the sub-packages for Radio/NoRH and Yohkoh/SXT. If these softwares were not installed, please contact your system manager. The primary distribution site for SolarSoftware is: `http://www.lmsal.com/solarsoft/` We define the top directory of SSW as `${SSW}` and that of NoRP subpackage as `${NORP}` (usually `${SSW}/radio/norp`) in this manual.

(2) Installation of *NoRP data base*

Copy the NoRP data base after getting them from the NRO solar archive at `ftp://solar.nro.nao.ac.jp/pub/norh/data`. The recommended destination is `${NORP}/data`.

(3) Setup of your personal environment

Include the followings in your environment setup file (`~/.cshrc`).

```
setenv SSW SSW-directory[1]
setenv SSW_INSTR ``norp''
source ${SSW}/gen/setup/setup.ssw
```

Note that the enviroment variable `${SSW}` can be different (Ask your system manager)[2] . In case you analyze many kinds of data at the same time, define SSW_INSTR as follows, e.g.

```
setenv SSW_INSTR ``sxt hxt norh norp''
```

4 Analysis

4.1 Start Analysis

The NoRP IDL procedures described in this section all depend on the SolarSoftware (SSW). When you start the analysis, start up the SSW/IDL as follows:

`unix%` **sswidl <CR>**

If you start up the SSW/IDL on the computers of Nobeyama Solar Radio Observatory, the start-up command is as follows:

`unix%` **idlh <CR>**

[1] `/share/ssw` in NRO

[2] In NRO, it is `/share/ssw`

4.2 Database

4.2.1 Event List

There is a data base for the events ('evx' data) from January 1990 to May 1992[3] . In order to list them, e.g. on June 9, 1991 UT,

IDL> **norp_pr_evx,'1991-06-09' <CR>**

From June 5, 1991 UT to June 8,

IDL> **st_day='1991-06-05' <CR>**
IDL> **ed_day='1991-06-08' <CR>**
IDL> **norp_pr_evx,st_day,ed_day <CR>**

For only strong events which have 1000 SFU peak flux in 17GHz,

IDL> **norp_pr_evx,st_day,ed_day,criterion=1000 <CR>**

4.2.2 Daily Averaged Flux

Daily averaged flux values after choosing non-flaring-time data are installed in the database (after November 1987). These data can be used for obtaining pre-flare flux or for studying the long-term variation.

Toyokawa (1, 2, 3.75, 9.4 GHz) : Nov 1987 – Feb 1994
Toyokawa (3.75 GHz only) : Mar 1994 – Apr 1994
Nobeyama (17, 35, 80 GHz) : Mar 1990 – Feb 1994
Nobeyama (1, 2, 3.75, 9.4, 17, 35, 80 GHz) : May 1994 – Present date
Note that the data for quiet Sun are fixed for 35 GHz (2400 SFU) and 80 GHz (9000 SFU) due to their instrumental limits.

In order to read the data, e.g. from Jan 1, 1999 to Jun 30,

IDL> **st_day='1999-01-01' <CR>**
IDL> **ed_day='1999-06-30' <CR>**
IDL> **norp_rd_avg,st_day,ed_day,timavg,fiavg,fvavg <CR>**

for plot, e.g. of 1GHz

IDL> **utplot,timavg,fiavg(0,*) <CR>**

of 2GHz

IDL> **utplot,timavg,fiavg(1,*) <CR>**

4.3 Where is the Data ?

4.3.1 Calibrated Data in XDR (IDL save) format

Some already-calibrated NoRP data are put in the NRO solar archive (see section A). You can obtain them by anonymous FTP. Before synthesizing by yourself, try them first. They are loaded into the IDL session by using the IDL command `restore`. There are 1-sec resolution data for steady observatin and 0.1-sec resolution data for events.

IDL> **file=getenv('NORP_XDR')+'/1999/08/norp19990828_0056.xdr' <CR>**
IDL> **restore,file <CR>**
IDL> **help <CR>**

```
DAY             STRING    = '1999-08-28'
FI              FLOAT     = Array[7, 7590]
FIAVG           FLOAT     = Array[7]
FREQ            FLOAT     = Array[7]
FV              FLOAT     = Array[7, 7590]
FVAVG           FLOAT     = Array[7]
MVD             BYTE      = Array[7, 7590]
TIM             STRUCT    = -> ANYTIM2INTS Array[7590]
```

`freq` is observing frequencies in units of GHz (in this example, 1, 2, 3.75, 9.4, 17, 3, 80 GHz), `tim` is observing time, `fi`,`fv` are I (R+L), V (R–L) comonents of flux density and `fiavg`, `fvavg` are daily average, respectively. `mvd` is an array including the values of unity (1) for valid data or zero (0) for non-valid data.

[3] For the events after June 1992, see the event list of Nobeyama Radioheliograph

4.3.2 Raw Data

Some raw NoRP data are put in the NRO solar archive (see section A). You can obtain them by anonymous FTP.

4.4 Read the Data — Nobeyama Radio Polarimeters

There are two kinds of formats for Nobeyama Radio Polarimeters (NoRP). One is before unifing with Toyokawa Radio Polarimeters and the other is after that. For older format, the files include only 1, 2, 3.75 9.4 GHz data.

In order to read the data into IDL session, give the date (JST) as follows:

`IDL>` **day='1991-1-25'**

`IDL>` **norp_rd_dat,day,mvd,tim,fi,fv,freq <CR>**

or give the file name as follows:

`IDL>` **file='/archive/pub/norp/raw/1991/01/pl910125'**

`IDL>` **norp_rd_dat,file,mvd,tim,fi,fv,freq <CR>**

`freq` is observing frequencies in units of GHz (in this example, 1, 2, 3.75, 9.4, 17, 3, 80 GHz), `tim` is observing time, `fi`,`fv` are I (R+L), V (R–L) comonents of flux density, respectively. `mvd` is an array including the values of unity (1) for valid data or zero (0) for non-valid data.

In order to read the data in specified duration:

`IDL>` **timerange=['1991-1-25 2:00','1991-1-25 4:00'] <CR>**

`IDL>` **norp_rd_dat,day,mvd,tim,fi,fv,freq,timerange=timerange <CR>**

In order to read the data of specified frequency, e.g. for 17 GHz,

`IDL>` **rdfreq=[0,0,0,0,1,0,0] <CR>**

`IDL>` **norp_rd_dat,day,mvd,tim,fi,fv,rdfreq=rdfreq <CR>**

For 1GHz and 9.4GHz,

`IDL>` **rdfreq=[1,0,0,1,0,0,0] <CR>**

`IDL>` **norp_rd_dat,day,mvd,tim,fi,fv,rdfreq=rdfreq <CR>**

Each element in the array `rdfreq` corresponds to the data of one frequency among 1, 2, 3.75, 9.4, 17, 35 and 80 GHz.

4.5 Read the Data — Toyokawa Radio Polarimeters

The Toyokawa Radio Polarimeters were observing in 4 frequencies, namely 1, 2, 3.75, and 9.4 GHz.

In order to read the data into IDL session, give the date (JST) as follows:

`IDL>` **day='1992-11-02'**

`IDL>` **tykw_rd_dat,day,mvd,tim,fi,fv,freq <CR>**

or give the file name as follows:

`IDL>` **file='/archive/pub/norp/raw/1992/11/ty921102.01i' <CR>** ; 1GHz I-component

`IDL>` **file0pa='/archive/pub/norp/raw/1992/11/ty921102.0pa' <CR>** ; 0PA calibration data

`IDL>` **filestt='/archive/pub/norp/raw/1992/11/ty921102.stt' <CR>** ; status data

`IDL>` **tykw_rd_dat,file,file0pa,filestt,mvd,tim,data <CR>**

`freq` is observing frequencies in units of GHz, `tim` is observing time, `fi`,`fv` are I (R+L), V (R–L) comonents of flux density, respectively. `mvd` is an array including the values of unity (1) for valid data or zero (0) for non-valid data.

In order to read the data in specified duration:

`IDL>` **timerange='1992-11-2 '+['1:00','2:00'] <CR>**

`IDL>` **tykw_rd_dat,day,mvd,tim,fi,fv,freq,timerange=timerange <CR>**

In order to read the data of specified frequency, e.g. for 9 GHz,

`IDL>` **rdfreq=[0,0,0,1] <CR>**

`IDL>` **tykw_rd_dat,day,mvd,tim,fi,fv,rdfreq=rdfreq <CR>**

For 1GHz and 9.4 GHz,

`IDL>` **rdfreq=[1,0,0,1] <CR>**

`IDL>` **tykw_rd_dat,day,mvd,tim,fi,fv,rdfreq=rdfreq <CR>**

Each element in the array `rdfreq` corresponds to the data of one frequency among 1, 2, 3.75, and 9.4 GHz.

4.6 Plot

For plotting,

IDL> **mfreq=0 <CR>**

IDL> **norp_plot,mfreq,mvd,tim,fi <CR>**

where `mfreq` is the index number of the plotting frequency in the array `freq`.

To overlay another plot

IDL> **mfreq1=1 <CR>**

IDL> **norp_plot,mfreq1,mvd,tim,fi,/over <CR>**

Or by directly; IDL> **utplot,tim(where(mvd(mfreq,*))),fi(mfreq,where(mvd(mfreq,*))) <CR>**

4.7 Spectrum Analysis

By coordinating multiple frequency observation, we may dervive the spectrum of the emission. The obtained variable is α whose definition is

$$F_\nu \propto \nu^\alpha.$$

In real, α is not uniform over the frequencies. But the spectrum in microwave range is approximately fitted by the fucntion in the form :

$$F_\nu = \widehat{F_\nu}\left(\frac{\nu}{\widehat{\nu}}\right)^{\alpha_{\rm tk}}\left\{1-\exp\left[-\left(\frac{\nu}{\widehat{\nu}}\right)^{\alpha_{\rm tn}-\alpha_{\rm tk}}\right]\right\} \approx \begin{cases} \widehat{F_\nu}\left(\nu/\widehat{\nu}\right)^{\alpha_{\rm tk}} & \text{for } \nu \ll \widehat{\nu} \\ \widehat{F_\nu}\left(\nu/\widehat{\nu}\right)^{\alpha_{\rm tn}} & \text{for } \nu \gg \widehat{\nu} \end{cases} \tag{1}$$

Here are 4 fitting parameters: $\widehat{\nu}$ is turn-over frequency, $\widehat{F_\nu}$ is turn-over flux density, $\alpha_{\rm tk}$ is power index of low frequency side (optically thick side) and $\alpha_{\rm tn}$ is power index of high frequency side (optically thin side), respectively. The procedures are as follows:

IDL> **day='2002-07-18'**

IDL> **timerange=['2002-07-18 3:30','2002-07-18 4:00'] <CR>**

IDL> **norp_rd_dat,day,mvd,tim,fi,fv,freq,timerange=timerange <CR>**

IDL> **norp_rd_avg,day,timavg,fiavg,fvavg <CR>**

IDL> **for m=0,6 do fi(m,*)=fi(m,*)-fiavg(m) <CR>**

IDL> **norp_alpha,freq,fi,mvd,mvdfit,alpha_tk,alpha_tn,freqpk,fluxpk <CR>**

After subtracting the pre-flare flux levels (here daily averages are used), the flare fluxes are given to the IDL procedure `norp_alpha`. `mvdfit` is an array including the values of unity (1) for valid data or zero (0) for non-valid data.

Note: The fitting will usually fail in the simple manner shown here. We need (1) to take longer intergation time for getting better S/N ratio and (2) to remove the inadequate data for fitting (because, say, the emission in that frequency is not due to gyrosynchrotron). See 4.8.3 for better procedures.

4.7.1 Optically-Thin Non-Thermal Gyrosynchrotron Emission (Preliminary)

Note: The procedures described in this subsection are under testing. Comments are welcome for improvement.

Based on approximation models, the relation between the physical variables of emitting region and the emission can be derived. The electron distribution function is assumed to be the power law.

$$\frac{dNV(E)}{dE} = K\left(\frac{E}{E_0}\right)^{-\delta}$$

where E is electron energy (keV), $NV(E)$ is number of electrons (particles) that has larger energy than E. This distribution is described with parameters δ, E_0, and K. But it is usual to use $NV(E_0) = K/(\delta-1)/E_0^{\delta-1}$ instead of K. And we fix $E_0 = 10$ keV after Dulk (1985).

(a) From Physical Variables to Emission

Inputs; power-law index δ, magnetic field strength (G), angle between magnetic field and line of sight (degree), and NV — total number (particles) of non-thermal electron (of $E > 10$ keV): Outputs; flux density (SFU), circular polarization degree:

By Dulk's (1985) method:

IDL> **dulk_gysy,delta,bb,theta,nv,freq,fi,rc <CR>**

If the size of emitting source (by solid angle in unit of sterad) is given additionally, optical depth is also obtained

IDL> **dulk_gysy,delta,bb,theta,nv,freq,fi,rc,omega,tau <CR>**

By Ramaty's (1969) method:

IDL> **ramaty_gysy,delta,bb,theta,nv,freq,fi,rc <CR>**

IDL> **ramaty_gysy,delta,bb,theta,nv,freq,fi,rc,omega,tau <CR>**

(b) From Emission to Physical Variables

Based on Dulk's (1985) model we may derive the physical variables from emission. After deriving α (see 4.7), power law index of non-thermal electron distribution function is

IDL> **norp_alpha,freq,fi,mvd,mvdfit,alpha_tk,alpha_tn,freqpk,fluxpk <CR>**

IDL> **norp_alpha2delta,alpha_tn,delta <CR>**

4.7.2 Optically-Thin Thermal Free-Free Emission (Preliminary)

Note: The procedures described in this subsection are under testing. Comments are welcome for improvement.

(a) From Physical Variables to Emission

Based on Dulk's (1985) approximation models, the relation between the physical variables of emitting region and the emission can be derived. Inputs; electron temperature (K), line-of-site component of magnetic field (G), and volume emission measure (cm^{-3}) Outputs; flux density (SFU), circular polarization degree:

IDL> **dulk_frfr,te,b_loc,vem,freq,fi,rc <CR>**

If the size of emitting source (by solid angle in unit of sterad) is given additionally, optical depth is also obtained

IDL> **dulk_frfr,te,b_loc,vem,freq,fi,rc,omega,tau <CR>**

4.8 Example of Analysis Session

4.8.1 Choose an Event

Many interesting events are introduced in NoRP web site. It is recommended to access first to these pages. The URL is

`http://solar.nro.nao.ac.jp/norp/`

4.8.2 Light Curves

After choosing an event for analysis, see the light curves. Calibrated data is already prepared in XDR (IDL save) format for important events. So restore it first,

IDL> **file=getenv('NORP_XDR')+'/1999/08/norp19990828_0056.xdr' <CR>**

IDL> **restore,file <CR>**

For plots,

IDL> **mfreq=0 <CR>**

IDL> **norp_plot,mfreq,mvd,tim,fi <CR>**

Here `mfreq` is the number of the data identifying the frequency. For overplotting another frequency data,

IDL> **mfreq1=1 <CR>**

IDL> **norp_plot,mfreq1,mvd,tim,fi,/over <CR>**

4.8.3 Spectrum Analysis

For deriving spectrum, it is better to integrate longer than default for getting better S/N ratio. In case integrating 300 points (30 sec),

IDL> **mint=300 <CR>**

IDL> **norp_mkint,mint,mvd,tim,fi,fv,mvdav,timav,fiav,fvav <CR>**

Next subtract pre-flare flux

IDL> **for m=0,6 do fiav(m,*)=fiav(m,*)-fiavg(m) <CR>**

Using this flux, fit the spectrum

IDL> **norp_alpha,freq,fiav,mvdav,mvdfit,alpha_tk,alpha_tn,freqpk,fluxpk <CR>**

Assuming gyrosynchrotron emission, the power-law index of non-thermal electrons is obtained

IDL> **norp_alpha2delta,alpha_tn,delta <CR>**

Sometimes fitting will fail if the observation data include some points extremely out of the fitting function. One reason is that the emission mechanism is different in the low frequency range (not gyrosynchrotron but plasma emission). Another reason is bad S/N ratio in high frequency observation, especially in 80 GHz. In this case, remove such data points from fitting as follwos:

IDL> **mvfreq=[2,3,4,5,6] <CR>**

IDL> **norp_alpha,freq(mvfreq),fiav(mvfreq,*),mvdav(mvfreq,*) $ <CR>**

IDL> **,mvdfit,alpha_tk,alpha_tn,freqpk,fluxpk <CR>**

In order to confirm that the fitting is well-done, plot the fitting function over the observation data. For example, for n-th data

IDL> **norp_funcp,alpha_tk(n),alpha_tn(n),freqpk(n) ,fluxpk(n),freqfit,fifit <CR>**

IDL> **plot,freq,fiav(*,n),/xlog,/ylog,psym=5 <CR>**

IDL> **oplot,freqfit,fifit <CR>**

4.9 Others

4.9.1 Read Raw Data Directly

In order to read raw data directly, for Nobeyama data

IDL> **file='/archive/pub/norp/raw/1991/01/pl910125' <CR>**

IDL> **norp_rd_rdt,file,rdata,date,version <CR>**

for Toyokawa data

IDL> **file='/archive/pub/norp/xdr/1992/04/tykw920402.xdr' <CR>**

IDL> **tykw_rd_rdt,file,rdata <CR>**

For obtaining observing time (JST) for Nobeyama data

IDL> **timej=norp_rdt2timej(rdata,date) <CR>**

A NoRP data archive: anonymous FTP

The Nobeyama Radio Observatory (NRO/NAOJ) has prepared the anonymous FTP server for the NoRP data archive. The URL is

`ftp://solar.nro.nao.ac.jp/pub/norp`

If you need to transfer a large amount of data , please contact

`service@solar.nro.nao.ac.jp`

We will make and mail a CD-ROM for you. The network capability in Nobeyama is limited.

B Acknowledgement

We thank the following people. SolarSoftware is a software package for analysis of Solar Data on IDL. That is supported under various NASA contracts (SXT/EIT/MDI/TRACE/YPOP etc.) and is all in the public domain. IDL is a product by Research System Inc.

References

Dulk, G. A., 1985, ARAA, **23**, 169

Nakajima et al. "The Radiometer and Polarimeters at 80, 35, and 17 GHz for Solar Observations at Nobeyama", PASJ, 37, 163 (1985)

Ramaty, 1969, ApJ, **158**, 753

Shibasaki et al. "Solar Radio Data Acquisition and Communication System (SORDACS) of Toyokawa

Observatory", Proc. of the Res. Inst. of Atmospherics, Nagoya Univ., 26, 117 (1979)
Torii et al. "Full-Automatic Radiopolarimeters for Solar Patrol at Microwave Frequencies", Proc. of the Res. Inst. of Atmospherics, Nagoya Univ., 26, 129 (1979)